

## Diesel Generating Sets

60  
Hz

## Model: SM1925

INDUSTRIAL RANGE

Powered by MTU



## Generating Rates

POWER RATING		PRIME	STANDBY
POWER	kVA	1750	1925
	kW	1400	1540
Rated Speed	r.p.m	1800	
Standard Voltage	V	480	
Available Voltages	V	480/277-440/254-220/127-208/120	
Rated at power factor	Cos Phi	0.8	

Ambient conditions of reference: 1000 mbar, 25°C, 30% relative humidity. Power according to ISO 3046 normative.

P.R.P. Prime Power - ISO 8528 : prime power is the maximum power available during a variable power sequence, which may be run for an unlimited number of hours per year, between stated maintenance intervals. The permissible average power output during a 24

Standby Power (ISO 3046 Fuel Stop power): power available for use at variable loads for limited annual time (500h), within the following limits of maximum operating time: 100% load 25h per year – 90% load 200h per year. No overload available. Applicable i



WWW.SUNSHINEGENERATOR.COM

## Diesel Generating Sets



## Model: SM1925

INDUSTRIAL RANGE

Powered by MTU

### Engine Specifications 1800 r.p.m.



ENGINE		CONTINUOUS	STANDBY		
Rated Output	kW	1520	1672		
Manufacturer		MTU			
Model		12V4000G43			
No. of Cylinders and Build		4 Cycle;12V Cylinder Diesel			
Aspiration and Cooling		Exhaust turbo charger and Air charge air cooling;			
Bore/Stroke	mm	170X210			
Compress the ratio		16.5			
Cooling system		Water-cooled			
Engine Speed/Frequency	rpm/Hz	1800/60HZ			
Coolant Capacity	L	520			
Starting System		Electric 24 volt DC			
Displacement	L	57.2			
Lubricant system Capacity	L	260			
Battery Volatge / Capacity		24VDC			
Governing Type	Type	Electronic engine management system "ADEC"			
Air Filter	Type	Dry			
Fuel Consumption	Load	100%	75%	50%	25%
	L/h	366.0	285.0	200.0	118.0

**ENGINE**--Industrial 4 stroke cooled diesel engine complete with air,fuel and oil filters,electric starting and charging equipment,engine protection against low water level.

**COOLING**--Radiator and colling fan complete with protection guards,designed to cool engine at specified output in air temperatures upto 45 °C ,radiators suitable for higher temperatures are available.Low water level protection fitted as standard.

**ELECTRICAL SYSTEM**--24V upto.Axial type starter motor,battery charging alternator,high capacity lead acid battery,and battery tray mounted on the generator base frame,and heavy duty interconnecting cable with terminations.

**EXHAUST SYSTEM**--Heavy duty industrial exhaust silencer with flexible piping.



WWW.SUNSHINEGENERATOR.COM

## Diesel Generating Sets

60 Hz

## Model: SM1925

INDUSTRIAL RANGE

Powered by MTU



## Alternator Technical Specifications

ALTERNATOR BRAND		LEROY SOMER	STAMFORD
Model			PI734C
Exciter System		Self-excited, brushless	
Poles	Num	4	
Cooling Fan		Cast alloy aluminum	
Bearing		Single,double shielded	
Windings		100% copper	
Connection Type		Reconnectable	
Insulation Type	Class	Class H	
Pitch		2/3	
Amortisseur Winding		Full	
Voltage Regulator		A.V.R. (Electronic)	
Steady Voltage Precision		± 1%	
Underspeed Protection		Standard	
Overexcitation Protection		IP23	
TIF (1960 Weightings)		<50	

**ALTERNATOR**--Brushless,self exciting,self regulation,sreen protected,drip proof rated in accordance with IEC60034.Voltage regulation maintainted within ±0.5% from no load to full load.between 0.8 lagging and unity.All standard voltages available.

## Diesel Generating Sets

60  
Hz

Model: **SM1925**

INDUSTRIAL RANGE

Powered by MTU

## Control Panel Technical Specifications

### Control Panel- ComAp AMF20

The base mounted control panel in a vibration isolated sheet steel enclosure. The control panel is equipped as follows:

- Instruments: Analogue Voltmeter, Hours Run Meter, Water pressure Meter.
- Controls: Emergency Stop Pushbutton, Voltmeter Phase Selector Switch.
- Control module: Standard collocation is ComAp AMF20 Auto start with AMF.



#### Main Features:

- Δ Automatic mains failure
- Δ Engine control, Generator protection
- Δ Built in alarms and warnings
- Δ Remote Start operation available
- Δ Daily / weekly / monthly exerciser
- Δ Weekly operation schedule programs
- Δ Fuel pump control
- Δ ECU control and monitoring via J1940 CANBUS
- Δ Mains simulation
- Δ Block heater control
- Δ Field adjustable parameters
- Δ Free MS-Windows Remote monitoring
- Δ LED displays
- Δ Configurable analogue inputs
- Δ I/O expansion capability



#### Protection Circuits

- WARNING
- Battery charge failure
- Low battery voltage
- SHUT DOWNS
- Fail to start
- Emergency stop
- Low oil pressure
- High engine temperature
- Over /Under speed
- Under/over generator frequency
- Failed to reach loading voltage
- ELECTRICAL TRIP
- Generator over current

#### Instruments

- ENGINE
- Engine speed
- Oil pressure
- Coolant temperature
- Run time
- Battery volts
- TOR
- Voltage (L-N)
- Current (L1-L2-L3)
- Frequency
- MAINS
- Voltage (L-L, L-N)



WWW.SUNSHINEGENERATOR.COM

## Diesel Generating Sets



**Model: SM1925**  
INDUSTRIAL RANGE  
Powered by MTU

## Generating Sets Standard Features

Three phase four wire, output voltage 480V/277V, 60HZ, between 0.8 lagging, protection capability according with the standard of NAME1 and IP23.

### General Features:

- Δ Composed of MTU diesel engine and Stamford or Leroy somer alternator
- Δ Oil and fuel filter fitted, water separator
- Δ Lube-oil drain valve fitted
- Δ Electric Starter Charge motor 24 V.D.C
- Δ Water-cooled
- Δ 8-hours operation base tank
- Δ Auto start
- Δ Optional soundproof and weatherproof canopy
- Δ 3 pole MCCB Delixi breaker
- Δ Operation & Maintenance manual
- Δ Special Integrated Steel Base tank and sprayed overall in gloss enamel paint

### Voltage Regulation:

- Voltage regulation maintained within  $\pm 0.5\%$
- Between 0.8 and 1.0 lagging and unity
- From no load to full load
- At speed droop variation upto 4.5%

### Frequency Adjustable Ratio:

Change load from 0-100%, within 1.0% ( electric speed regulator), within 4.5% ( mechanical speed regulator)

### Frequency Undulation:

- load from 0-100%, frequency undulation within 0.25%
- No load wire volts max undulation ration\ within 1.8%
- Three Phrase balanced load in the order of 5%
- Effect factor of Telecom
- TIF better than 50
- THF to IEC60034 Part 40 better than 2%



WWW.SUNSHINEGENERATOR.COM

## Diesel Generating Sets

60  
Hz

Model: **SM1925**

INDUSTRIAL RANGE

Powered by MTU

## Soundproofed Version Features

### Robust Corrosion Resistant Construction

- Δ Black finish stainless steel lock and hinges
- Δ Body made from steel components treated with polyester powder coating

### Excellent Access for Maintenance

- Δ Two large doors on each side
- Δ Radiator fill access plate
- Δ Lube oil and cooling water drains pipes to exterior of the enclosure

### Security and Safety

- Δ Control panel viewing window in a lockable access door
- Δ Emergency stop push button (red) mounted on enclosure interior
- Δ Cooling fan and battery charging alternator fully guarded
- Δ Exhaust silencing system totally enclosed for operator safety





WWW.SUNSHINEGENERATOR.COM

## Diesel Generating Sets



**Model: SM1925**  
INDUSTRIAL RANGE  
Powered by MTU

## Generating Sets other Features

### Generating Sets Optional Features

- ΔLow fuel level alarm shutdown
- ΔAutomatic Fuel Filling System
- ΔEngine oil feeding and drain pump
- ΔAuto Transfer Switch( ATS)
- ΔParallel control panels
- ΔCircuit Breaker MCCB & ACB
- ΔRemote Control Panel
- Δweatherproof/soundproof Canopy
- ΔTrailer type Gensets

### Quality Standards

ISO9001:2000,ISO14000,ISO3046  
ISO8528 BS4999  
BS5514,AS1359,ICE34  
CE Compliance

### Gensets Dimensions & Weight

Open type:LxWxH (mm) Net Weight Kgs

5350\*2110\*2660 / 9500

Open type:LxWxH (mm) Net Weight Kgs

40' Standard Container / 19500



FUZHOU SUNSHINE MACHINERY CO.,LIMITED  
Fuzhou, Fujian, China.

Tel:86-591-88204179 FAX:86-591-87723357

Email: sales@sunshinemach.com www.sunshinegenerator.com



WWW.SUNSHINEGENERATOR.COM

SUNSHINE reserves the right to modify the characteristics of its product at any time in order to incorporate the latest technological developments. The information contained in this document may therefore be changed without notice.